



## DESCRIPTION





### LUMINAIRE BODY

- Aluminum injection body with a high dissipation performance, COOL TECH technology, warranty of a higher performance and a long lasting product life.
- Stem made of anodized aluminum and equipment-carrier box body in semicrystalline thermoplastics.
- Stem in a silver anodized color.
- Under request custom stem length and body color
- Electronic converter (driver) integrated in the equipment-carrier box.
- Main voltage 220-240V 50/60Hz. F.P:  $\phi = 0,95$
- Installation: for installation on universal three-phase rail updated according to standard.
- Body with an elegant and compact design, created exclusively to integrate high-performance LED light sources.
- The orientation system allows 355° rotation from the vertical axis and 90° tilt from the horizontal one.
- Useful life: L80B50: 70.000 hours/L70B10: 100.000 hours. Ta:25°C

### OPTICS

- Well-defined and clean light beams for an efficient accent lighting in shops, showrooms and sales.
- Textured lens: color consistency throughout the pattern: ring effects are eliminated and the color temperature does not change with the LED emission angle.
- SPOT (16°), FLOOD (23°) and SUPERFLOOD (31°) spotlights with PHI-REFLECTOR® technology, thanks to its facet design it allows a higher control of the light beam with a minimum dispersion of light, obtaining the maximum definition of the projected beam.
- Configuration HIGH CONTRAST, with a smooth reflector with EFFICIENT technology with FRESNEL lens, that manages to eliminate diffuse light around the beam.
- Limitation of light depreciation thanks to the incorporation of a protection diffuser at the light output, the optical component is protected from external agents.
- LED RETAIL EVO special, CRI > 95 color reproduction and a higher selection of binning for a correct color reproduction, free of adding color to White color objects, textile or other materials. Add a special phosphorous that achieves a good balance in the appearance of colors and white

## CURVES



## LUMINAIRE

### LOGAR CMH RETAIL · LED rail SPOTLIGHT with a special LED RETAIL

Light source	W	Color temp. (K)	Colour	CRI	Output	Kg	Reference
<b>HIGH CONTRAST</b>							
LED930+	28	3.000	Oxiron black	95	1.000 lm	1	81203PV9300PPOX
LED930+	28	3.000	Matt white	95	1.000 lm	1	81203PV9300PPBM
<b>SPOT 16°</b>							
LED930+	28	3.000	Oxiron black	95	2.050 lm	1	81203PV9300SPOX
LED930+	28	3.000	Matt white	95	2.050 lm	1	81203PV9300SPBM
<b>FLOOD 23°</b>							
LED930+	28	3.000	Oxiron black	95	1.950 lm	1	81203PV9300FLOX
LED930+	28	3.000	Matt white	95	1.950 lm	1	81203PV9300FLBM
<b>SUPERFLOOD 31°</b>							
LED930+	28	3.000	Oxiron black	95	1.800 lm	1	81203PV9300SFOX
LED930+	28	3.000	Matt white	95	1.800 lm	1	81203PV9300SFBM

## DIMENSIONS

